

Technical Data Sheet

Dokumental® CF 57xx Highlighter Inks

Water based, Dye-Based Highlighter Inks with Extended Cap-Off Time

General Information

The dye-based highlighter inks of Dokumental® CF 57xx series are optimized for an extended cap-off time. Furthermore they are extremely brilliant when used on standard papers.

Suitable Surfaces

Compatible with standard papers. Colour fading or colour changing might occur if used on acid paper in combination with high air humidity.

Physical Data

Type	Colour	Viscosity at 20°C mPa s ± 0.5	Surface tension mN/m ± 2.0	Density at 20°C g/cm ³ ± 0.01	pH-Value
Dokumental® CF 5700	yellow	3.7	36.0	n.d.	10.1 - 12.1
Dokumental® CF 5712	yellow green	3.6	35.8	n.d.	10.0 - 12.0
Dokumental® CF 5724	orange	3.3	41.2	n.d.	2.8 - 3.8
Dokumental® CF 5746	pink	3.8	40.3	n.d.	5.0 - 7.0
Dokumental® CF 5750	blue	2.5	40.9	n.d.	4.7 - 5.7

Technical Advice

Suitable Components

Nibs: polyester, foamed polyethylene with high porosity

Reservoirs: polyester, polypropylene (acetate reservoirs are not compatible with these inks).

Barrels, Caps, Plugs: polypropylene, ABS, butadiene-styrene, polyethylene.

It is mandatory to approve the compatibility of the ink and the components as well as the performance of the writing system in advance.

Cap and plug of the marker must close tightly.

All plastic parts should be made of material with low vapour permeability. Polypropylene and butadiene-styrene (BS) is most suitable.

Before use of our product the filling station has to be maintained and cleaned carefully. The inks are sensitive to any kind of contamination (e.g. chemical or microbial contaminations). Cross-contamination of the inks may lead to a colour mismatch or will even lead to a defective marker or shorter shelf life.

The inks contain biocides to prevent microbial growth, but for best protection we additionally recommend to ensure best hygienic conditions in production areas as well as cleanliness of all marker components.

Due to the high pH-value of some inks the compatibility with the nibs has to be tested.

Storage, Handling & Transportation

Store our product frost protected and avoid direct sunlight. Recommended storage temperature for the product is between

10°C and 30°C. Storage temperatures above 30°C for several days bear the risk of a reduced shelf life of the ink.

The shelf life of the inks in original sealed containers is two years. Make sure that the drums are closed tightly after they were opened.

Applicable Standards & Regulations

Unless expressly agreed, no warranty is given that all standards & regulations relevant to the Customer's intended use have been and will be complied with. To the extent that compliance with certain standards & regulations is warranted, this warranty shall only apply at the time the underlying contract is entered into. There is no guarantee that the products will continue to comply with the standards & regulations in the event of future changes. Dokumental also assumes no obligation to inform the Customer of any changes to such standards & regulations that may be relevant to the Customer.

Packaging

20 kg plastic drum
 200 kg plastic drum
 1,000 kg IBC

Produced by

DOKUMENTAL GmbH & Co KG
 Wöllnerstraße 26
 D-67065 Ludwigshafen
 Phone: +49(0)621/37702-200
 Mail: info@dokumental.de
www.dokumental.de